BRYANT® Permanently Marked Receptacles

for Automatic Outlet Control Systems

Power when you need it... Energy savings when you don't

- Permanent power symbol remains clearly visible after installation
- Control both outlets per device for 100% controlled applications or just one outlet for 50% controlled applications
- Ideal for commercial buildings, retail, schools, hotel rooms
- Available in duplex and decorator styles
- Part of the Bryant Load:Logic™ Plug Control system. Visit www.bryant-electric.com for details

Bryant permanently marked receptacles for automatic outlet control systems are embossed with the universally recognized ⏻ power symbol and the word "**CONTROLLED**." These markings clearly identify which convenience outlets are turned off when the workspace is vacant.

Automatic Outlet Control systems are required for at least 50% of the receptacles installed in private offices, open offices, and computer classrooms.

BRYANT® Permanently Marked Receptacles

Permanently Marked Receptacles for use with Automatic Outlet Control Systems

		One Controlled Face Split Circuit Hot Tab ⏻		Two Controlled Faces ⏻ ⏻	
Description	Colors*	15A	20A	15A	20A
Standard Duplex Smooth nylon face, back and side wired.	Black	**CBRS15C1BLK**	**CBRS20C1BLK**	**CBRS15C2BLK**	**CBRS20C2BLK**
	Brown	**CBRS15C1**	**CBRS20C1**	**CBRS15C2**	**CBRS20C2**
	Gray	**CBRS15C1GRY**	**CBRS20C1GRY**	**CBRS15C2GRY**	**CBRS20C2GRY**
	Ivory	**CBRS15C1I**	**CBRS20C1I**	**CBRS15C2I**	**CBRS20C2I**
	Light Almond	**CBRS15C1LA**	**CBRS20C1LA**	**CBRS15C2LA**	**CBRS20C2LA**
	White	**CBRS15C1WHI**	**CBRS20C1WHI**	**CBRS15C2WHI**	**CBRS20C2WHI**
Decorator Duplex Smooth nylon face, back and side wired.	Black	**DRS15C1BLK**	**DRS20C1BLK**	**DRS15C2BLK**	**DRS20C2BLK**
	Brown	**DRS15C1**	**DRS20C1**	**DRS15C2**	**DRS20C2**
	Gray	**DRS15C1GRY**	**DRS20C1GRY**	**DRS15C2GRY**	**DRS20C2GRY**
	Ivory	**DRS15C1I**	**DRS20C1I**	**DRS15C2I**	**DRS20C2I**
	Light Almond	**DRS15C1LA**	**DRS20C1LA**	**DRS15C2LA**	**DRS20C2LA**
	White	**DRS15C1WHI**	**DRS20C1WHI**	**DRS15C2WHI**	**DRS20C2WHI**

**Note: Blue, Green and Red are available as a made to order. Consult factory for details.*

CBRS15C1WHI

CBRS20C2LA

DRS20C1GRY

DRS20C2I

MSCUHD

Permanent Controlled Receptacle Label

For use in retrofit applications where indication of a controlled receptacle is required. This label is UL approved for marking and labeling. 60 labels of each per pack.	**BCL60**

Heavy Duty Control Unit

Robust latching relay provides reliable performance over many different applications, including plug loads. 20A 100-277V AC, 1HP @ 120V AC, 2HP @ 240/277V AC. Auto or Manual-ON operation. Powers up to six low voltage sensors.

Description	Voltage	Catalog Number
Heavy duty control unit	100-277V AC	**MSCUHD**
Heavy duty latching relay, for use with MSCUHD		**MSAR20P**

Note: Visit www.bryant-electric.com for technical specifications and wiring schematics.

Codes and Standards

2014 National Electric Code®	ASHRAE Energy Efficiency Standard 90.1 2010	California Title 24 2013
2014 Section 406.3 (E) requires that all non-locking, 125V, 15A and 20A receptacles controlled by an automatic control device or by an automatic energy management system must be marked with the ⏻ symbol.	Standard 90.1-2010 requires that 50 percent of all 125V, 15A and 20A receptacles in private offices, open offices, and computer classrooms be controlled by an automatic control device. Controlled receptacles need to be marked to differentiate them from non-controlled receptacles.	California Title 24 2013 requires that in all buildings, both controlled and uncontrolled 120V receptacles shall be provided in each private office, open office area, reception lobby, conference room, kitchenette in office spaces, and copy room.

Bryant® Electric • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484 • Phone (800) 323-2792 • FAX (800) 543-0538

Printed in U.S.A. Specifications subject to change without notice.
® is a registered trademarks of Hubbell Incorporated.

BLDSB003 3/16